



The small workgroup solution with big productivity advantages. Fast print copy/performance. Full-function faxing. Scanning options to move information faster. Powerful finishing options for in-house, on-demand printing. All at a competitive cost, with Minolta **Di2010f**.



- High-speed, high-output productivity: up to 20ppm
- Modular finishing options: sort, group, staple, hole-punch, saddle-stitch, center crease
- Super G3 fax for high-speed transmission/reception, 11" x 17" fax capability, optional Internet faxing for fast fax distribution
- Dual line multiport option, large memory, autodialing features
- Easy upgrades to support high-speed printing, scanning, expanded memory
- Optional Reversing Auto Document Feeder, optional duplexing with 100% duplex productivity
- New tilting control panel with on-screen QWERTY keyboard
- 4,000-sheet maximum paper capacity, durable paper drawers, 150-sheet intelligent bypass (standard)
- Point-and-click desktop printing with Minolta's internal Print Controller options
- Optional scanning to convert paper documents to digital files – scan to FTP, URL, E-mail, HDD, IP Scanner
- Powerful PageScope software to control documents and devices anywhere on your network  
 PageScope Light  
 PageScope Network Setup  
 PageScope Net Care  
 PageScope NDPS Plug-Ins  
 PageScope EMS Gateway  
 PageScope ABU  
 PageScope Cabinet Pro  
 PageScope Router (optional)
- Recollect® software for fast scanning, auto OCR, electronic filing, one-touch retrieval (optional)
- Electronic Forms Management for replacing greenbar forms (optional)

**DiALTA Di2010f Digital Printer/Copier/Scanner/Fax**





## Di2010f Specifications

**TYPE:**  
Digital Printer/Copier/Scanner/Fax

**COMMUNICATION LINE:**  
Public Switched Telephone Network (PSTN)

**COMPATIBILITY:**  
G3, Super G3

**DATA COMPRESSION:**  
MH, MR, MMR, JBIG

**SCANNING SYSTEM:**  
CCD Line Sensor

**MODEM SPEED:**  
33.6 Kbps (max; automatic fallback)

**TRANSMISSION SPEED:**  
Less than 3 seconds per page

**SCANNING SPEED:**  
Up to 70 sheets per minute (with AFR-19 Reversing Auto Document Feeder)

**DIALING:**  
540 one touch dialing

**BROADCAST:**  
300 destinations

**IMAGING SYSTEM:**  
Electrostatic Dry Powdered Image Transfer to Plain Paper

**DEVELOPMENT SYSTEM:**  
Minolta Micro-Toning High-Grade (MT-HG)

**SCANNING SYSTEM:**  
CCD Line Sensor

**PRINT/COPY SPEED:**  
20 ppm (letter) 8-1/2" x 11" portrait  
17 ppm (letter) 8-1/2" x 11" landscape  
14 ppm (legal) 8-1/2" x 14"  
12 ppm (ledger) 11" x 17"

**PRINT/COPY RESOLUTION:**  
True 600 x 600 dpi

**FAX RESOLUTION:**  
200 x 100 dpi  
200 x 200 dpi  
400 x 400 dpi  
Text/Photo (400 x 400 dpi)  
Grayscale (200 x 200 dpi)  
Super Grayscale (400 x 400 dpi)

**HALFTONE REPRODUCTION:**  
256 gradations

**MEMORY:**  
32 MB 170 pages (standard)  
40 GB 2,000 pages (maximum)

**FAX MEMORY:**  
Up to 1,400 pages (standard)  
Up to 2,000 pages (maximum)

**WARM-UP TIME:**  
17 seconds

**FIRST COPY:**  
5.3 seconds or less

**COPY QUANTITY:**  
1 - 99 copies (countdown, interrupt capability)

**MAGNIFICATION:**  
Zoom range: 25 - 400%, 1% increments  
Preset reduction: 50%, 65%, 73%, 79%, 93%  
Preset enlargement: 121%, 129%, 155%, 200%

**EXPOSURE MODES:**  
Auto  
Text  
Photo  
Text/Photo  
Manual

**ORIGINAL SIZE:**  
Up to 11" x 17" maximum

**PAPER SIZE:**  
5-1/2" x 8-1/2" to 11" x 17"

**FAX TRANSMISSION/RECEPTION SIZE:**  
Up to 11" x 17"

**PAPER WEIGHT:**  
15 lb. to 24 lb. bond; 15 lb. to 24 lb. recycled paper

**PAPER WEIGHT VIA MANUAL BYPASS:**  
24-1/4 lb. to 55-3/4 lb. specialty paper  
(thick paper, OHP transparencies, postcards, ten #10 envelopes, label sheets)

**STANDARD PAPER SUPPLY:**  
550-sheet universal paper drawers (2)  
150-sheet intelligent bypass

**OPTIONAL PAPER SUPPLY:**  
550-sheet universal paper drawer and storage drawer  
550-sheet universal paper drawers  
(2 drawers, 1,100-sheet capacity)  
2,750-sheet tandem drawer (letter)

**MAXIMUM PAPER CAPACITY:**  
4,000 sheets (total, with options)

**DOCUMENT FEEDER:**  
**AFR-19** Reversing Auto Document Feeder  
Capacity: 80 sheets  
Speed: up to 70 ppm  
Original size: up to 11" x 17"  
1-sided, 2-sided originals  
Mixed original detection

**POWER REQUIREMENTS:**  
120V, 60Hz, 11.5A

**POWER CONSUMPTION:**  
1340 w (max.)

**DIMENSIONS (WxDxH):**  
26-3/4" x 28" x 28-1/4"

**WEIGHT:**  
163 lbs.

## PageScope Applications

**NETWORK AND DEVICE MANAGEMENT:**  
PageScope Light  
PageScope Net Care  
PageScope Network Setup  
PageScope EMS Plug-Ins  
PageScope NDPS Gateway  
PageScope ABU

**DOCUMENT WORKFLOW MANAGEMENT:**  
PageScope Cabinet Pro  
PageScope Router

## Di2010f Options

OC-6 Original Cover  
AFR-19 Reversing Auto Document Feeder  
PF-122 Large Capacity Cabinet (2,750 sheets letter portrait)  
PF-124 Universal Paper Feed Cabinet (550 sheets, letter to ledger size) plus storage drawer  
PF-210 Universal Two-Way Paper Feed Cabinet (1,100 sheets, letter to ledger size)  
CD-4M Copy Desk  
AD-16 Duplex Unit (only on Di2010/Di2010f)  
SB-1 Switchback Unit (only on Di2010/Di2010f)  
JS-203 Job Separator Tray  
FN-117 Finisher  
AK-1 Additional Bin Kit  
MK-1 Mailbin Kit  
PK-6 Punch Kit  
SK-1 Saddle Kit  
Pi3505e PCL Print Controller  
Pi3505e PostScript 3 + PCL Print Controller  
Parallel Interface Kit (IEEE 1284)  
NC-4 Network Printer Kit  
HDD-6 Hard Disk Drive  
SU-2, SU-3 Scanning Options  
32MB, 64MB, 128MB Memory Upgrades  
MP-5 Dual Line Multiport  
Tx Marker Stamp Unit  
Spare Tx Marker Stamp

## Pi3505e PCL Specifications

**TYPE:**  
Internal

**PROCESSOR:**  
233MHz

**MEMORY:**  
32MB (standard)

**INTERFACE TO NETWORK:**  
Parallel (IEEE 1284 compatibility)  
RJ45 (Ethernet 10/100 BaseT) + USB Port  
Token Ring (3rd party)

**NETWORK PROTOCOLS:**  
TCP/IP, IPP, Novell IPX/SPX, SNMP, NDS (Novell Directory Services), Peer-to-Peer (TCP/IP, IPX/SPX), LPR/LPD (TCP/IP), HTTP, Netware, SMTP/POP3

**PRINT DRIVERS:**  
PCL6 driver for Windows 98/ME, NT4.0, Windows 2000, Windows XP  
PCL5e mini driver for Windows 98/ME, NT4.0, Windows 2000, Windows XP

## Pi3505e PostScript 3 + PCL Specifications

**TYPE:**  
Internal

**PROCESSOR:**  
233MHz

**MEMORY:**  
128MB (standard)

**INTERFACE TO NETWORK:**  
Parallel (IEEE 1284 compatibility)  
RJ45 (Ethernet 10/100BaseT) + USB Port  
Token Ring (3rd party)

**NETWORK PROTOCOLS:**  
TCP/IP, IPP, Novell IPX/SPX, SNMP, NDS (Novell Directory Services), Peer-to-Peer (TCP/IP, IPX/SPX), LPR/LPD (TCP/IP), HTTP, Netware, SMTP/POP3

**PRINT DRIVERS:**  
PostScript Level 3 Driver for MAC OS 9.2, 10.2+  
PPD File, PDF-Direct Print/Font Download Utility for WIN/MAC  
PCL6 driver for Windows 98/ME, NT4.0, Windows 2000, Windows XP  
PCL5e mini driver for Windows 98/ME, NT4.0, Windows 2000, Windows XP

## SU-2 Scan Option Specifications

**SCAN FUNCTIONS:**  
Scan-to-FTP, HDD, E-Mail, URL, Network TWAIN

**MEMORY:**  
128MB (standard)

**SCAN FORMATS:**  
TIFF, PDF

**RESOLUTION:**  
Up to 600 X 600 dpi

## SU-3 Scan Option Specifications

**SCAN FUNCTIONS:**  
Scan-to-FTP, HDD, E-Mail, URL, IP Scanner, Internet Faxing, Network TWAIN

**MEMORY:**  
128MB (standard)

**SCAN FORMATS:**  
TIFF, PDF

**RESOLUTION:**  
Up to 600 X 600 dpi

## Available Facsimile Functions \*

Auto Dialing (540 locations)  
Auto/Manual Dialing  
Batch Transmission  
Book Scanner Transmission  
Broadcast (300 locations)  
Confidential Mailbox Transmission/Reception  
Delayed Broadcast

## Available Facsimile Functions Continued \*

Delayed Transmission (up to 24 hours)  
Fax Print and/or Forward  
Fax Reduction (100% - 60% in both directions)  
F-Code support  
Group Broadcasting  
Internet Faxing  
Memory Backup  
Memory Lock/Memory Receive  
Multi-Access  
Multiple TSI Settings  
Polling Transmission/Reception  
Priority Transmission  
Program Keys (30)  
Quick Memory Transmission  
Remote Copying  
Selective Polling Reception  
Selective Polling Transmission (up to 10 bulletin boards)  
Timer Transmission (up to 200 timers)  
Transmission Marker  
Transmission Rotation

## Available Print/Copy Functions \*

APS/AMS  
Auto Duplex, Stackless (option)  
Auto/Manual/Photo Exposure  
Auto Tray Switching  
Black-White Reverse  
Book Copy  
Booklet Pagination  
Copy Track (up to 1,000 accounts)  
Cover Mode  
Criss/Cross Sorting  
Energy Save Mode  
Erase (border, frame, edge)  
Face-Up or Face-Down Output  
Hole-Punching (2-hole, 3-hole)  
Image Repeat  
Image Rotation  
Image Stamping  
Interrupt (pause)  
Job Memory (10 jobs)  
Job Reserve (queue) (10 jobs)  
Memory Recall  
OHP Interleave  
Page Insertion  
Scanning (E-mail, FTP, HDD, URL notification, IP Scanner, Internet Faxing)  
Separate Scanning  
Stamping Distribution (continuous distribution number)  
Stapling (single or multi-position)  
Storyboarding (2-in-1, 4-in-1)  
Text, Photo, Text/Photo Modes  
XY Zoom



Always Use Genuine  
Minolta Supplies

© 2003 KONICA MINOLTA HOLDINGS, INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Minolta, DiALTA, PageScope, and The essentials of imaging are trademarks of KONICA MINOLTA HOLDINGS, INC. Recollect is a registered trademark of Rebus Technology. All other brands and product names are registered trademarks or trademarks of their respective owners.

Design & specifications are subject to change without notice.

\* Some functions may require options, which may or may not be available at time of launch.

KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. • 100 Williams Drive • Ramsey, NJ 07446  
[www.minoltausa.com](http://www.minoltausa.com)  
[www.minoltausa.com/solutions](http://www.minoltausa.com/solutions)

